

VALCO CINCINNATI CONSUMER PRODUCTS INC.
MATERIAL SAFETY DATA SHEET
MATERIAL NAME: VALCO PHASE 2 (710XX766, 710XX768)
EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053
PRODUCT INFORMATION NO.: (513) 874-6550
DATE ISSUED: AUGUST 2009

SECTION I – GENERAL INFORMATION

MANUFACTURER'S NAME: VALCO CINCINNATI, INCORPORATED
ADDRESS: 411 CIRCLE FREEWAY DRIVE, CINCINNATI, OHIO 45246

IDENTITY: VALCO PHASE 2 - TIRE AND RUBBER DRESSING
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION: N/A
HEALTH (NFPA): N/A **FLAMMABILITY (NFPA):** N/A **REACTIVITY (NFPA):** N/A
REVISION: N/A
DOT: N/A
SHELF LIFE: 3 YEARS

SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY - COMMON NAME(S)):

ODORLESS MINERAL SPIRITS 67-73%

CAS NUMBER: 64741-65-7

OSHA PEL: N/A

ACGIH TLV: N/A

TLV/STEL: N/A

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT 345-406°F

FREEZE POINT: N/A

SPECIFIC GRAVITY 0.8

VAPOR PRESSURE: N/A

VAPOR DENSITY (AIR = 1): >1

SOLUBILITY IN WATER, % BY WEIGHT: <0.1

PERCENT VOLATILES BY VOLUME: 70-75%

EVAPORATION RATE <1 (N-BUTYL ACETATE=1)

FLASH POINT: N/A

pH (NEAT): N/A

APPEARANCE AND ODOR: MOSTLY TRANSPARENT CLEAR

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): 125°F(TCC)

FLAMMABLE LIMITS IN AIR BY VOLUME: N/A

EXTINGUISHING MEDIA: DRY, CHEMICAL, OR CARBON DIOXIDE OR FOAM OR SAND/EARTH OR HALON.

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF-CONTAINED BREATHING APPARATUS (POSITIVE PRESSURE). THIS MATERIAL IS COMBUSTIBLE AND MAY BE IGNITED BY HEAT, SPARKS, FLAME OR OTHER SOURCES OF IGNITION (e.g. STATIC ELECTRICITY, PILOT LIGHTS, MECHANICAL/ELECTRICAL EQUIPMENT.)

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

SECTION V – REACTIVITY DATA

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL CONDITIONS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, AND/OR CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INCOMPATIBLE MATERIALS: AVOID STRONG ACIDS AND BASES, OXIDIZING AGENTS AND SELECTED AMINES

SECTION VI – HEALTH HAZARD DATA

ROUTES OF ENTRY: EYES, SKIN, INGESTION, INHALATION

EYE: CAUSES MODERATE IRRITATION AND PAIN

SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION AND DERMATITIS.

INHALATION: CAUSES NASAL AND BRONCHIAL IRRITATION.

INGESTION: ASPIRATION HAZARD IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE.

PERMISSIBLE CONCENTRATIONS (AIR):

100 PPM ACGIH TWA

100 PPM OSHA TWA

VALCO CINCINNATI CONSUMER PRODUCTS INC.
MATERIAL SAFETY DATA SHEET
MATERIAL NAME: PHASE 2 (710XX766, 710XX768)
EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053
PRODUCT INFORMATION NO.: (513) 874-6550
DATE ISSUED: AUGUST 2009

SECTION VI – HEALTH HAZARD DATA (CONT)

EMERGENCY AND FIRST AID PROCEDURES:

EYES: MOVE VICTIM FROM EXPOSURE AND INTO FRESH AIR. IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF FLOWING WATER FOR A LEAST 15 MINUTES AND CALL A PHYSICIAN.

SKIN: WASH WITH WARM SOAPY WATER. REMOVE CONTAMINATED CLOTHING. IF IRRITATION OCCURS, GET MEDICAL ATTENTION

INGESTION: ASPIRATION HAZARD: DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. IF VICTIM IS DROWSY OR UNCONSCIOUS, PLACE ON LEFT SIDE WITH HEAD DOWN. CALL A PHYSICIAN IMMEDIATELY.

INHALATION: REMOVE VICTIM TO FRESH AIR AND CALL MEDICAL PERSONNEL IMMEDIATELY. IF NOT BREATHING GIVE MOUTH TO MOUTH RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ABSORB WITH AN INERT MATERIAL SUCH AS SAND, SOIL, OR VERMICULITE: SWEEP UP AND DISPOSE OF MATERIAL IN ACCORDANCE WITH ALL LAWS, FEDERAL, STATE AND LOCAL.

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS AT TIME OF DISPOSAL.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP AWAY FROM FOODSTUFFS. WASH THOROUGHLY AFTER USE. DO NOT EAT, DRINK, OR SMOKE WHILE USING. SAFETY SHOWER, EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE.

OTHER PRECAUTIONS: NONE

SECTION VII – CONTROL MEASURES

RESPIRATORY PROTECTION: USE NIOSH/OSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IF VAPOR CONCENTRATION EXCEEDS PERMISSIBLE EXPOSURE LIMIT.

VENTILATION: GENERAL VENTILATION IS RECOMMENDED. DO NOT BREATHE VAPORS AND AVOID CONTACT WITH EYES AND SKIN. IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED LIMITS (SEE SECTION VI) ADDITIONAL VENTILATION EXHAUST SYSTEMS MAY BE REQUIRED. WHERE EXPLOSIVE MIXTURES MAY BE PRESENT, ELECTRICAL SYSTEMS SAFE FOR SUCH LOCATIONS MUST BE USED.

PROTECTIVE EQUIPMENT: USE SOLVENT RESISTANT RUBBER OR PLASTIC GLOVES, SAFETY GLASSES. IF CLOTHING IS CONTAMINATED, REMOVE CLOTHING AND THOROUGHLY WASH THE AFFECTED AREA. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

SECTION IX – DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE; OBTAINED FROM SOURCES BELIEVED BY VALCO CINCINNATI, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCT ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THIS PRODUCT OR THE INFORMATION PROVIDED HERE WITH.